

Europäisches Patentamt

European Patent Office

Office européen des brevets



(11)

EP 1 201 485 A1

(12)

## EUROPEAN PATENT APPLICATION

(43) Date of publication:

02.05.2002 Bulletin 2002/18

(51) Int Cl.7: B60L 11/12, B60L 11/18

(21) Application number: 01000394.5

(22) Date of filing: 21.08.2001

(84) Designated Contracting States:

AT BE CH CY DE DK ES FI FR GB GR IE IT LI LU  
MC NL PT SE TR

Designated Extension States:

AL LT LV MK RO SI

(72) Inventor: GABRIEL, David

48047, NEW BALTIMORE (US)

(74) Representative: Messulam, Alec Moses

A. Messulam &amp; Co. Ltd.,

43-45 High Road

Bushey Heath, Bushey, Herts WD23 1EE (GB)

(30) Priority: 08.09.2000 US 659018

(71) Applicant: FORD MOTOR COMPANY

Dearborn, MI 48121 (US)

## (54) HEV charger/generator unit

(57) The present invention provides an apparatus, system, and method of utilising a home power unit ("HPU") which functions as a battery charger for a hybrid electric vehicle ("HEV") or as a generator, utilising the HEV's electrical power to operate external electrical devices. In its simplest form, the HPU comprises a transformer, inverter means, rectifier means, a control unit, connection means to the HEV and external electrical loads or sources and switching means to change operation between charger and generator function. Alterna-

tive embodiments of the present invention utilise the HEV's existing components thereby avoiding component redundancy within the HPU. Specifically, in the first alternative embodiment, the inverter means are utilised within the vehicle, therefore, requiring only filter and transformer to be added to the vehicle. In the second alternative embodiment, the vehicle's DC-to-DC converter is utilised as opposed to implementing a transformer. Therefore, only an inverter and filter are added to the system.




Fig-4

## Description

[0001] The present invention relates to a home power unit for hybrid electric vehicles ("HEVS") that acts as a general charger for the vehicle's battery and as a generator to operate external electrical devices, such as power tools.

[0002] The need to reduce fossil fuel consumption and pollutants of automobiles and other vehicles powered by internal combustion engines ("ICES") is well known. Vehicles powered by electric motors have attempted to address these needs. However, electric vehicles have limited range and limited power coupled with the substantial time needed to recharge their batteries. An alternative solution is to combine both an ice and electric traction motor into one vehicle. Such vehicles are typically called hybrid electric vehicles ("HEVS"). See generally, U.S. Pat. No. 5,343,970 (Severinsky).

[0003] The HEV has been described in a variety of configurations. Many HEV patents disclose systems where an operator is required to select between electric and internal combustion operation. In other, the electric motor drives one set of wheels and the ice drives a different set.

[0004] Other configurations have developed. A series hybrid electric vehicle ("SHEV") is a vehicle with an engine (most typically an ice) which powers a generator. The generator, in turn, provides electricity for a battery and motor coupled to the drive wheels of the vehicle. There is no mechanical connection between the engine and the drive wheels. A parallel hybrid electrical vehicle ("phev") is a vehicle with an engine (most typically an ice), battery, and electric motor combined to provide torque to power the wheels of the vehicle.

[0005] A parallel/series hybrid electric vehicle ("PSHEV") has characteristics of both a PHEV and a SHEV. The PSHEV is also known as a torque (or power) splitting powertrain configuration. Here, the torque output of the engine is given in part to the drive wheels and in part to an electrical generator. The electric generator powers a battery and motor that also provide torque output. In this configuration, torque output can come from either source or both simultaneously. In this configuration the vehicle braking system can even deliver torque to drive the generator to produce charge to the battery.

[0006] As the HEV continues to develop, new challenges are encountered and new uses are developed. One of the main challenges associated with all HEV's is insuring enough battery charge to start and operate the vehicle. All batteries lose charge as a result of use or lapse of time. Generally, the HEV battery is charged by an ice generator in the vehicle; however, during unusual conditions or emergencies, external battery charging may be necessary.

[0007] A potential use for the HEV is to utilise its battery and generator as a source of electrical power to operate electrical devices such as power tools. This type of vehicle use for auxiliary electrical power is well known

for conventional ice vehicles. Specifically, many patents have been issued utilising the components of ices as a power source for electrical devices. For example, U.S. Patent no. 3,824,404 (Leonard Ghery); U.S. Patent no. 3,953,740 (Charles Seiter, Jr.); U.S. Patent no. 4,074,145 (p. Laffoon, et al.); And U.S. Patent 5,066,866 (William Hallidy), disclose various methods of utilising a vehicle's alternator to generate AC voltage to power electrical devices. However, these patents do not apply to HEV's because the HEV does not require an alternator. The HEV already has a ready source of electrical power within its battery and can generate additional power with an onboard generator. However, the HEV's electrical power, needs to be converted for external use by electrical devices.

[0008] The present provides a method, system, and apparatus for charging an HEV battery and utilising the HEV as a generator to operate external electrical devices. The apparatus will be referred to as a home power unit ("HPU") combining these two functions.

[0009] The HPU, as a charger, provides the user with the ability to charge the HEV's battery during emergency or unusual conditions. Generally, the battery is charged through the operation of an onboard generator in combination with the engine. If the onboard high voltage battery charge depletes completely, the engine would not be able to start. Therefore, it is necessary to have a way to charge a HEV battery. The present invention provides just such a means.

[0010] The HPU also operates as a generator allowing a user to draw upon the vehicle's electrical power to run external electrical devices. The HPU draws power from the HEV's generator and to some extent, its battery. The HPU converts this power to a useable form for external electrical devices such as power tools.

[0011] In both modes, the HPU functions as a conversion device to convert external AC electrical power sources to DC power for charging the HEV battery (charger function) or convert on board DC electric power to AC electric power (generator function). In both modes the HPU is also capable of converting from one desired voltage to another (i.e., From low 110 to high 300 or reverse). In its simplest form, the HPU apparatus comprises a transformer to convert electrical voltages, inverter means to convert DC to AC, rectifier means to convert AC to DC, a control unit, a connection means to connect to the HEV and external electrical loads or sources, and a switching means to change operation between the charger and the generator functions. The apparatus connects to external loads or services through connection means with the transformer. The HPU then connects to the HEV's high voltage DC bus and system controllers, specifically, a battery electronic control unit. The switching devices for the HPU may comprise a momentary two position switch on the instrumental panel, a menu selection from an on-screen display mounted in the instrumental panel or a two position switch mounted on the HPU.

[0012] In an alternative embodiment, the HPU is incorporated directly into the components of the HEV. In this manner, redundant components are avoided. Particularly, in the first alternative embodiment, the HPU inverter means are already within the vehicle, specifically a traction inverter. A contactor is implemented between the traction inverter and the motor to switch the power source from the vehicle function (going to the motor) to the HPU function (operating as a generator and proceeding to a filter).

in another alternative embodiment, HEV components are again implemented as opposed to installing a separate HPU unit to avoid redundancy. In this second alternative embodiment, a DC-to-DC converter is utilised as opposed to the transformer. The inverter/rectifier means are then implemented after the DC-to-DC converter to provide the appropriate current changes.

[0013] The invention will now be described further, by way of example, with references to the accompanying drawings, in which:

Fig. 1 illustrates the general layout of a hybrid electric vehicle,

Fig. 2 illustrates the home power unit's implementation into a hybrid electrical vehicle,

Fig. 3 demonstrates the layout of the home power unit,

Fig. 4 illustrates an alternative embodiment of the HPU utilising some of the hybrid electric vehicle's existing components, and

Fig. 5 illustrates a second alternative embodiment of the HPU utilising some of the hybrid electric vehicle's existing components.

[0014] The present invention provides a unified apparatus, system and method for emergency charging of the vehicle's battery and utilising the power storage and generating capabilities of the vehicle to run external electrical devices. The present invention combines charger functions, with the ability to use the vehicle's generator and battery, to some limited extent, to operate external electrical devices. The present invention is referred to as a home power unit ("HPU"). In its simplest form, the HPU is a separate component that performs electrical conversions from AC-to-DC or DC-to-AC and from one voltage to another (ex., 110 volt to 300 volt or 300 volt to 110 volt).

[0015] Figure 1 demonstrates one configuration for a parallel/series hybrid electric vehicle ("torque splitting") configuration. The basic makeup of the vehicle includes: an engine 20 connected to a planetary gear 26 through a one way clutch. The planetary gear 26, splits the engine 20 output energy into a series path, from the engine 20 to a generator motor 24, and a parallel path, from the engine 20 to driving wheels 34. The engine speed can be controlled by varying the split to the series path, while maintaining the mechanical connection through the parallel path. The generator motor 24 is connected to a gen-

erator brake 45. The generator motor 24 is connected to the battery 28, and is capable of charging the battery 28. The electric motor 30, augments the engine on the parallel path through a second gear set 32. The motor also provides the opportunity to use energy directly from the series path, essentially drawing from the power created by the generator motor 24, thereby reducing the losses associated with converting energy into and out of chemical energy in the battery 28.

[0016] Many components in this configuration are controlled by vehicle system controller ("VSC") 36. The VSC 36, operate all the vehicle's main components by connecting to each components' controllers. The VSC 36 also contains the powertrain control module ("PCM"). These two "separate" controllers are housed in the same unit. The VSC/PCM 36 is then connected to the engine 20. The VSC 36 is also connected to a battery control unit ("BCU") 38, and a transmission management unit ("TMU") 40 through a communication network. The BCU 38 is then connected to the battery 28. The TMU 40 is connected to a generator controller 42 and a motor controller 44. The generator controller 42 is then connected to the generator motor 24 and the motor controller 44 is connected to the motor 30.

[0017] Figure 2 demonstrates the general configuration of an HEV utilising the HPU. An HPU 50, is connected to a vehicle's high voltage DC bus 58, and to a vehicle's battery control unit 54 ("BCU") through control circuits 60. The BCU 54 is then connected to a communication network 70 which is linked to an instrumental cluster 62, a transaxle controller 66 and a vehicle system controller 64. The battery unit 52 includes the batteries, the BCU 54 and a contactor box 56, which connects the battery to the high voltage DC bus 58.

[0018] Figure 3 demonstrates the internal components of the HPU. An HPU 80 includes a transformer 82 that is connected to a rectifier 84 and an inverter 86. The HPU 80 is operated by an internal control unit 88, which is connected to the rectifier 84 and the inverter 86. The internal control unit 88 also connects to a vehicle's control system 90, specifically the battery control unit. The transformer 82 connects to an external source/load 92, (typically a power outlet or an electric power device). Finally, lines to/from the rectifier 84 and the inverter 86 are connected within the HPU 80 and then connected to a vehicle's high voltage DC bus 94.

[0019] The HPU 80 operates as a two-way conduit in which the vehicle is placed into charging mode or generator mode by the user. The use of the HPU 80 would be dependent upon sufficient safety measures within the vehicle control systems. For example, the HPU 80 can require the vehicle's gear selector to be in park, the doors shut, and the parking brake to be applied before activating. Further, activation of the HPU 80 is communicated to all control modules on the communication network 70 to prohibit vehicle movement during HPU operation.

[0020] The HPU 80 can be activated through a variety

of means including a momentary two position switch mounted on an instrument panel, a menu selection from an on-screen display mounted on the instrument panel, or a two position switch mounted on the HPU itself. HPU 80 activation and switch position (which dictates HPU use as either charger or generator), is relayed to the battery electric control unit (vehicle control system 90) through the HPU's control unit 88.

[0021] Referring again to figure 3, the HPU, as previously described, can operate in two modes. In the first mode, the HPU operates as a charger. In this case, the HPU 80 is connected to an external source 92 (e.g., 110 volt AC) which is run into the transformer 82. The transformer 82 converts the source into the desired AC voltage, if necessary (e.g., 110 volt AC to 300 volt AC). The transformer 82 then sends the AC source to the rectifier 84 where it is converted to DC source (300 volt DC). The rectifier 84 then sends the DC source to the vehicle's high voltage DC bus 94 to charge the HEV's battery.

[0022] In generator mode, the HPU 80 utilises the vehicle's high voltage DC power source to produce useable a/c voltage. Specifically, the HPU 80 would be connected to the vehicle's high voltage DC system 94. In providing a DC source, the HEV draws upon the generator from the hybrid powertrain or, to, some limited extent, the vehicle's battery. The high voltage DC source (300 volt DC) would go through the HPU inverter 86 where the DC source is converted to an AC source (300 volt DC to 300 volt AC). The AC source continues to the transformer 82 where the source is converted from high voltage AC to a desirable, usable AC voltage (300 to 110 volt). Upon finishing this step, the HPU 80 connects to any external electrical device requiring the available (110 volt) AC source.

#### Alternative embodiment #1

[0023] In an alternative embodiment, the HPU utilises vehicle components to avoid component redundancy. Specifically, this embodiment provides a means for using the HEV as a "generator" without adding a separate HPU unit to the vehicle.

[0024] Figure 4 illustrates this embodiment. A generator 100 is connected to an engine (typically an ICE) to generate electrical power. The generator 100 is connected to a generator inverter 102 which converts the AC source to DC. Both the generator inverter 102 and a high voltage battery 106 are connected to a DC bus 104. The DC bus 104 is also connected to a traction inverter 108. In a normal HEV, the traction inverter 108 then connects to a traction motor 116; however, the present invention, in an attempt to utilise the components previously described would add a contactor 110 between the traction motor 116 and the traction inverter 108. The contactor 110 would then be connected to a filter 112 which is connected to a transformer 114. The transformer 114 could then connect to external loads.

[0025] The operation of this embodiment is similar to

that previously described. In this case the traction inverter 108, which is already part of the HEV, is utilised in place of adding a separate inverter within a HPU. However the traction inverter 108 will require a unique operating strategy to operate with the HPU. The traction inverter 108 converts the high voltage DC source to AC (300 volt DC to 300 volt AC). This is normally done to run the traction motor 116. The contactor 110 operates as a switch, directing the high voltage AC source to the traction motor 116 or the additional "HPU" components. Specifically, if the generator function of the HPU is selected, the contactor 110 directs the high voltage AC source to the filter 112, where noise is removed. The high voltage AC source is then sent to the transformer 114 which converts the AC source to AC voltage useable by external electrical devices (300 volt AC to 110 volt AC).

#### Alternative embodiment #2

[0026] In a second alternative embodiment, different HEV components are used to achieve the same HPU results. Figure 5 illustrates the second embodiment.

[0027] A generator 130 is attached to the engine to help generate electrical power. The generator 130 output is feed to a generator inverter 132 where the electrical power is converted to DC. The generator inverter 132 and a high voltage battery 134 are connected to a high voltage DC bus 136. The DC bus 136 is then connected to a DC-to-DC converter 138. The DC-to-DC converter 138 converts the high voltage DC source to a low voltage DC source (300 volt DC to 110 volt DC). The DC-to-DC converter 138 is then connected to an inverter 140 to convert the DC source to AC (110 volt DC to 110 volt AC). The inverter 140 is then connected to a filter 142 to remove any signal noise. Finally the filter 142 can connect to any external electric device.

[0028] In this second embodiment, power is drawn through the dedicated DC-to-DC converter 138 and inverter 140 only when the ICE is being used to turn the generator 130 to generate electricity. This minimises cycling the high voltage battery. It should also be noted that the DC-to-DC converter 138 and inverter are cooled to allow them to handle large AC electrical loads.


[0029] With this second embodiment, the unit may also operate as a charger. DC-to-DC converter technology is advancing and new two way converters exist. If a two way DC-to-DC converter is applied, and a rectifier is added to the inverter 140, the unit could be used to charge the HEV's high voltage battery 134. Specifically, the filter 134 would be connected to a external AC source. This source would then pass through a rectifier, which would be located where the inverter 140 is and converts the AC source to a DC source. The rectifier connects to the DC-to-DC converter 138 to convert the low voltage DC source to high voltage DC source. The DC-to-DC converter 138 attaches to the high voltage DC bus 136 which is attached to the high voltage battery

134.


the step of employing energy safety features to insure safe operation.

# Claims


1. Apparatus to act as a battery charger or generator in a hybrid electric vehicle ("HEV") comprising: a transformer (82) to convert electrical voltages; inverter means (86) to convert DC to AC; rectifier means (84) to convert AC to DC; a control unit(88); connection means to connect to the HEV and external electrical loads or an electrical source; and switching means to change operation between the function of charging and generating.
2. An apparatus as claimed in claim 1, wherein the transformer (82) is connectable through the connection means to external electrical loads or sources.
3. An apparatus as claimed in claim 1 wherein the rectifier (84) and inverter (86) connect to a high voltage DC bus in the HEV.
4. An apparatus as claimed in claim 1 wherein the control unit (88) connects to a vehicle control system (90) in the HEV.
5. An apparatus as claimed in claim 4 wherein the control unit (88) connects to a battery electronic control unit (54) of the HEV.
6. An apparatus as claimed in claim 1 wherein the switching means comprises a momentary two position switch on an instrument panel (62).
7. An apparatus as claimed in claim 1 wherein the switching means comprises a menu selection from a on-screen display mounted on the instrument panel(62).
8. An apparatus as claimed in claim 1 wherein the switching means comprises a two position switch.
9. A method of using the apparatus of any one of the preceding claims to function as a battery charger or generator comprising the steps of; operating the switching means to select the functions of charging or generating; communicating the selected function and operation to the HEV; and converting an electric source from AC to DC (charging function) or DC to AC (generator function).
10. A method as claimed in claim 9 further comprising; converting voltage sources from one voltage to another.
11. A method as claimed in claim 9 further comprising
12. A hybrid electric vehicle (HEV) operable as a power source to operate external electrical devices comprising; an engine (20) to drive a generator(100); to create electrical power; inverter/rectifier means (102,108) to convert electrical sources from AC to DC or DC to AC; a high voltage DC bus (104)to connect switching means (110) to alter the electrical power flow from a vehicle traction function to a power supply function; and, connection means to connect the HEV to external electrical devices.
13. A vehicle as claimed in claim 12 further comprising; a transformer (114) to convert voltage sources.
14. A vehicle as claimed in claim 12 wherein the inverter/rectifier means (102,108) comprises; a generator inverter (102) to convert AC power from the generator (100) to DC power for the high voltage DC bus (104); and, a traction inverter (108) that converts DC power from the high voltage DC bus (104) to AC power for the switching means (110).
15. A vehicle as claimed in claim 12 further comprising filter means (112) to remove signal noise from electrical sources.
16. A vehicle as claimed in claim 12 wherein the switching (110) means comprises a contactor (110) that routes AC power from the traction inverter (108) to a traction motor(116), or the filter (112).
17. A vehicle as claimed in claim 12, further comprising voltage converter means (138) to convert from one voltage level to another.
18. A vehicle as claimed in claim 17 wherein the voltage converter (138) comprises a DC-to-DC converter.
19. A vehicle as claimed in claim 17 further comprising a filter (142) to remove electrical noise.





**Fig-1**



**Fig-2**



**Fig-3**







European Patent  
Office

## EUROPEAN SEARCH REPORT

Application Number  
EP 01 00 0394

DOCUMENTS CONSIDERED TO BE RELEVANT			
Category	Citation of document with indication, where appropriate, of relevant passages	Relevant to claim	CLASSIFICATION OF THE APPLICATION (Int.Cl.7)
X	DE 199 35 873 A (ZAHNRADFABRIK FRIEDRICHSHAFEN) 1 March 2001 (2001-03-01)	1-3, 8-10, 12	B60L11/12 B60L11/18
Y	* the whole document *	6, 7, 11, 13-15, 17-19	
Y	EP 1 067 648 A (DEERE & CO) 10 January 2001 (2001-01-10) * abstract * * paragraph '0017! *	6	
Y	US 6 275 231 B1 (OBRADOVICH MICHAEL L) 14 August 2001 (2001-08-14) * abstract * * figures 12-16 * * column 2, line 2 - line 47 *	7	
Y	EP 0 603 778 A (FUJI ELECTRIC CO LTD) 29 June 1994 (1994-06-29) * abstract * * column 2, line 57 - column 3, line 9 * * column 8, line 27 - line 38 * * column 11, line 19 - line 24 * * figure 7 *	11, 13	TECHNICAL FIELDS SEARCHED (Int.Cl.7) B60L H02J
Y	EP 1 110 799 A (SIEMENS AG) 27 June 2001 (2001-06-27) * abstract *	14, 17, 18	
Y	US 5 952 812 A (MAEDA NOBORU) 14 September 1999 (1999-09-14) * abstract *	15, 19	
A	DE 197 22 644 C (AEG ANGLO BATTERIES GERMANY GM) 17 September 1998 (1998-09-17) * the whole document *	1, 9, 12	
The present search report has been drawn up for all claims			
Place of search THE HAGUE		Date of completion of the search 27 February 2002	Examiner Hurtado-Albir, J
CATEGORY OF CITED DOCUMENTS X: particularly relevant if taken alone Y: particularly relevant if combined with another document of the same category A: technological background O: non-written disclosure P: intermediate document T: theory or principle underlying the invention E: earlier patent document, but published on, or after the filing date D: document cited in the application L: document cited for other reasons & member of the same patent family, corresponding document			



European Patent  
Office

# EUROPEAN SEARCH REPORT

Application Number  
EP 01 00 0394

DOCUMENTS CONSIDERED TO BE RELEVANT			
Category	Citation of document with indication, where appropriate, of relevant passages	Relevant to claim	CLASSIFICATION OF THE APPLICATION (Int.Cl.7)
A	DE 42 05 331 A (AUDI NSU AUTO UNION AG) 26 August 1993 (1993-08-26) * the whole document *	1, 9, 12	
A	PATENT ABSTRACTS OF JAPAN vol. 1999, no. 12, 29 October 1999 (1999-10-29) & JP 11 178241 A (MITSUBISHI ELECTRIC CORP), 2 July 1999 (1999-07-02) * abstract *	1, 9, 12	
			TECHNICAL FIELDS SEARCHED (Int.Cl.7)
The present search report has been drawn up for all claims			
Place of search: <b>THE HAGUE</b>		Date of completion of the search <b>27 February 2002</b>	Examiner: <b>Hurtado-Albir, J</b>
<p><b>CATEGORY OF CITED DOCUMENTS</b></p> <p>X : particularly relevant if taken alone Y : particularly relevant if combined with another document of the same category A : technological background O : non-written disclosure P : intermediate document</p> <p>T : theory or principle underlying the invention E : earlier patent document, but published on, or after the filing date D : document cited in the application L : document cited for other reasons &amp; : member of the same patent family, corresponding document</p>			

**ANNEX TO THE EUROPEAN SEARCH REPORT  
ON EUROPEAN PATENT APPLICATION NO.**

EP 01 00 0394

This annex lists the patent family members relating to the patent documents cited in the above-mentioned European search report. The members are as contained in the European Patent Office EDP file on The European Patent Office is in no way liable for these particulars which are merely given for the purpose of information.

27-02-2002

Patent document cited in search report		Publication date	Patent family member(s)	Publication date
DE 19935873	A	01-03-2001	DE 19935873 A1	01-03-2001
EP 1067648	A	10-01-2001	US 6281600 B1	28-08-2001
			AU 4262800 A	04-01-2001
			EP 1067648 A2	10-01-2001
US 6275231	B1	14-08-2001	AU 8589198 A	22-02-1999
			EP 1008133 A2	14-06-2000
			WO 9906987 A2	11-02-1999
			US 2002008718 A1	24-01-2002
EP 0603778	A	29-06-1994	JP 3178146 B2	18-06-2001
			JP 6245327 A	02-09-1994
			CA 2111726 A1	26-06-1994
			DE 69303150 D1	18-07-1996
			DE 69303150 T2	13-02-1997
			EP 0603778 A1	29-06-1994
			KR 151737 B1	15-04-1999
			US 5629603 A	13-05-1997
EP 1110799	A	27-06-2001	EP 1110799 A2	27-06-2001
US 5952812	A	14-09-1999	JP 10215522 A	11-08-1998
DE 19722644	C	17-09-1998	DE 19722644 C1	17-09-1998
			FR 2767095 A1	12-02-1999
			GB 2325799 A	02-12-1998
DE 4205331	A	26-08-1993	DE 4205331 A1	26-08-1993
JP 11178241	A	02-07-1999	NONE	